

SIDE-OPENING KNOCK-OUT PUNCH Réf.: **8017030001**

Caracteristics

The resistance of the tubes is between 162 and 180 kg / mm². These can be used for the cutting of soft materials (rubber, leather, felt, foam, Teflon, ...) as for that of materials reinforced with fiberglass or steel ... (up to 0, 3 mm). Knock the end with a mallet or rubber mallet. Striking area: forged and tempered. Heat treatment: hardness 52 HRC. Chamfer anti-shine. Cut: lateral opening Hardness 52 HRC. Finishing: phosphated surfaces. Knurl of 50 mm wide on the periphery. Dimension indicated by a durable cold stamped marking.



Product data

Ø mm	Artikelnr.	EAN Code
4	8017040001	3303808017049
5	8017050001	3303808017056
6	8017060001	3303808017063
7	8017070001	3303808017070
8	8017080001	3303808017087
10	8017100001	3303808017100



NOVALIA SAS 2 rue de Bergognon 42500 LE CHAMBON F.
FRANCE - www.novalia.pro
PEDDINGHAUS Handwerkzeuge In der Graslake 35
58332 Schwelm DEUTSCHLAND - www.peddinghaus.de
NOVALIA SA Str. Narciselor nr.50 500251 - Braşov ROMÂNIA
www.mob-ius.ro
NOVALIA ESPAÑA Portuete 51, of.204 20018 San Sebastián